

WHAT IS CLAIMED IS:

1. A wireless computer system comprising:

a base storage and control system including:

an arrangement for receiving and using an input
5 signal in real-time, the input signal being for use in
interacting with an application program being executable at
the base storage and control system,

an arrangement for providing non-volatile storage of
information,

10 an arrangement for providing a display output signal
based on the input signal and execution of the application
program, and

an arrangement for wirelessly receiving the input
signal and for wirelessly communicating the display output
15 signal in real-time;

at least one portable input-output system for use with
the base storage and control system, the portable input-output
system including:

an arrangement for wirelessly communicating the
20 input signal to the base storage and control system and for
wirelessly receiving the display output signal from the base
storage and control system in real-time,

an arrangement for inputting an information item and
for generating the input signal corresponding to the

0994521 "112601

information item, the input signal being wirelessly communicable in real-time to the base storage and control system for use in providing interactive and real-time operation of the application program being executable at the base storage and control system, and

an arrangement for providing a full screen display by directly using the display output signal to generate a portion of the full screen display corresponding to the display output signal;

wherein the application program is operable in real-time in the base storage and control system in essentially the same way that the application program is operable in a computer having a display and a keyboard, the display and the keyboard being coupled by wires to the computer.

2. The wireless computer system of claim 1, wherein at least one of a radio frequency signal and an electromagnetic frequency signal is used as a communication signal, the communication signal containing at least one of the input signal and the output display signal and being communicable by at least one of the arrangement for wirelessly receiving the input signal and for wirelessly communicating the display output signal and the arrangement for wirelessly communicating

0994521.112601

the input signal to the base storage and control system and for wirelessly receiving the display output signal.

3. The wireless computer system of claim 2, wherein:

5 the communication signal has a wavelength longer than an infrared signal wavelength, and

the communication signal includes at least one of a modulated signal, an amplitude modulated signal, a frequency modulated signal, and a spread spectrum modulated signal.

10

4. The wireless computer system of claim 1, wherein the output display signal includes at least one of a video signal, a video synchronizing signal, a horizontal video synchronizing signal, a vertical video synchronizing signal, a composite video signal, a video and synchronizing signal, and an RGB signal.

15

5. The wireless computer system of claim 1, wherein the input signal is a keyboard signal.

20

6. The wireless computer system of claim 1, wherein:

the input signal is a keyboard signal and the output display signal includes at least one of a video signal, a video synchronizing signal, a horizontal video synchronizing

09994524 1112604

signal, a vertical video synchronizing signal, a composite video signal, a video and synchronizing signal, and an RGB signal.

5 7. The wireless computer system of claim 1, wherein at least the input signal is an asynchronous signal.

8. The wireless computer system of claim 1, wherein at least one of the arrangement for wirelessly receiving the
10 input signal and for wirelessly communicating the display output signal and the arrangement for wirelessly communicating the input signal to the base storage and control system and for wirelessly receiving the display output signal includes:

an antenna;

15 an arrangement for demodulating a communicated signal corresponding to at least one of the input signal and the output display signal; and

an arrangement for modulating at least one of the input signal and the output display signal.

20

9. The wireless computer system of claim 8, wherein at least one of the arrangement for wirelessly receiving the input signal and for wirelessly communicating the display output signal and the arrangement for wirelessly communicating

the input signal to the base storage and control system and for wirelessly receiving the display output signal includes: a directional coupler, the directional coupler being coupled to the antenna, the arrangement for demodulating and the
5 arrangement for modulating.

10. The wireless computer system of claim 1, wherein at least one of the arrangement for wirelessly receiving the input signal and for wirelessly communicating the display
10 output signal and the arrangement for wirelessly communicating the input signal to the base storage and control system and for wirelessly receiving the display output signal includes:
an arrangement for communicating at least one of the input signal and the output signal omnidirectionally.

15

11. The wireless computer system of claim 1, wherein at least one of the arrangement for wirelessly receiving the input signal and for wirelessly communicating the display
output signal and the arrangement for wirelessly communicating
20 the input signal to the base storage and control system and for wirelessly receiving the display output signal includes a transceiver.

0994521 112601

12. The wireless computer system of claim 1, wherein the base storage and control system includes a microprocessor.

13. The wireless computer system of claim 1, wherein one of the at least one portable input-output system includes a microcontroller coupled to the arrangement for inputting an information item.

14. The wireless computer system of claim 1, wherein:
the base storage and control system includes a microprocessor; and

one of the at least one portable input-output system includes a microcontroller coupled to the arrangement for inputting an information item.

15. The wireless computer system of claim 1, wherein the arrangement for wirelessly receiving the input signal and for wirelessly communicating the display output signal is housed in a housing and the base storage and control system, except for the arrangement for wirelessly receiving, is housed in another housing, the housing and the another housing being electrically coupled.

16. The wireless computer system of claim 1, wherein:

the base storage and control system includes an interface arrangement for receiving graphics information being generated by executing the application program and for providing the graphics information to the at least one portable input-output
5 by using the arrangement for wirelessly communicating the display output signal; and

the at least one portable input-output includes another interface arrangement for providing the graphics information to the arrangement for providing a full screen display.

10

17. The wireless computer system of claim 16, wherein for an existing full screen display at the at least one portable input-output, the base storage and control system provides new graphics information for a changed portion of the
15 existing full screen display.

18. The wireless computer system of claim 1, wherein:

the at least one portable input-out system is a plurality of portable input-output systems; and

20

the base storage and control system is operable for establishing a priority of communication among the plurality of portable input-output systems with the base storage and control system.

0994521-112601

19. The wireless computer system of claim 1, wherein one of the at least one portable input-output includes a keyboard and a video display monitor.

5 20. The wireless computer system of claim 1, wherein the arrangement for providing non-volatile storage of information includes at least one of a disk drive and a CD-ROM.

21. A wireless computer system comprising:
 10 a base storage and control system including:
 means for receiving and using an input signal in real-time, the input signal being for use in interacting with an application program being executable at the base storage and control system,
 15 means for providing non-volatile storage of information,
 means for providing a display output signal based on the input signal and execution of the application program, and
 means for wirelessly receiving the input signal and
 20 for wirelessly communicating the display output signal in real-time;
 at least one portable input-output system for use with the base storage and control system, the portable input-output system including:

0994521-112601

means for wirelessly communicating the input signal to the base storage and control system and for wirelessly receiving the display output signal from the base storage and control system in real-time,

5 means for inputting an information item and for generating the input signal corresponding to the information item, the input signal being wirelessly communicable in real-time to the base storage and control system for use in providing interactive and real-time operation of the
10 application program being executable at the base storage and control system, and

means for providing a full screen display by directly using the display output signal to generate a portion of the full screen display corresponding to the display output
15 signal;

wherein the application program is operable in real-time in the base storage and control system in essentially the same way that the application program is operable in a computer having a display and a keyboard, the display and the keyboard
20 being coupled by wires to the computer.

22. A base storage and control system for use in a wireless computer system and for use with at least one portable input-output system for use with the base storage and

09994521 " 112601

control system, the portable input-output system including an arrangement for wirelessly communicating the input signal to the base storage and control system and for wirelessly receiving a display output signal from the base storage and control system in real-time, an arrangement for inputting an information item and for generating the input signal corresponding to the information item, the input signal being wirelessly communicable in real-time to the base storage and control system for use in providing interactive and real-time operation of an application program being executable at the base storage and control system, and an arrangement for providing a full screen display by directly using the display output signal to generate a portion of a full screen display corresponding to the display output signal, the base storage and control system comprising:

an arrangement for receiving and using the input signal in real-time, the input signal being for use in interacting with an application program being executable at the base storage and control system;

an arrangement for providing non-volatile storage of information;

an arrangement for providing the display output signal based on the input signal and execution of the application program; and

an arrangement for wirelessly receiving the input signal and for wirelessly communicating the display output signal in real-time;

wherein the application program is operable in real-time
5 in the base storage and control system in essentially the same way that the application program is operable in a computer having a display and a keyboard, the display and the keyboard being coupled by wires to the computer.

0994521 "112601
10 23. A portable input-output system for use in a wireless computer system with a base storage and control system, the base storage and control system including an arrangement for receiving and using an input signal in real-time, the input signal being for use in interacting with an application
15 program being executable at the base storage and control system, an arrangement for providing non-volatile storage of information, an arrangement for providing a display output signal based on the input signal and execution of the application program, and an arrangement for wirelessly
20 receiving the input signal and for wirelessly communicating the display output signal in real-time, wherein the application program is operable in real-time in the base storage and control system in essentially the same way that the application program is operable in a computer having a

display and a keyboard, the display and the keyboard being coupled by wires to the computer, the portable input-output system including:

an arrangement for wirelessly communicating the input
5 signal to the base storage and control system and for wirelessly receiving the display output signal from the base storage and control system in real-time;

an arrangement for inputting an information item and for
generating the input signal corresponding to the information
10 item, the input signal being wirelessly communicable in real-time to the base storage and control system for use in providing interactive and real-time operation of the application program being executable at the base storage and control system; and

15 an arrangement for providing a full screen display by directly using the display output signal to generate a portion of the full screen display corresponding to the display output signal.